## Claims

Sub.

1. A pressure-sensitive tape for closing, sealing and gluing joints in house construction, particularly joints in corners and edges, with a backing layer on the upper side of the tape and an adhesive layer, which is on the underside of the tape and provided with a protective film, wherein the protective film has at least one slit in the longitudinal direction and the tape is folded upon itself in the transverse direction along the slit in such a manner, that at least a portion of the protective film is disposed on the outside and that at least a lateral longitudinal section is provided, which is perforated.

- 2. The tape of claim 1, wherein the tape is slit twice and folded along one of the slits in the transverse direction.
- 3. The tape of claims 1 or 2, wherein the backing consists of paper and/or a plastic film and the adhesive layer is a pressure-sensitive acrylate adhesive.
- 4. The tape of one of the preceding claims, wherein the backing is such, that it can be torn by hand transversely to the longitudinal direction of the tape.
- 5. The tape of one of the preceding claims, wherein the adhesive layer has a non-adhering central strip and the protective film is slit along a line between the non-adhering central strip and the adjoining adhesive layer and is folded along the line.
- 6. The tape of one of the preceding claims, wherein the tape, in a folded state, is rolled up into a roll of adhesive tape.
- 7. The tape of claim 6, wherein an intermediate layer is provided at least at the folded side of the roll.

8. The tape of one of the preceding claims, wherein the tape is rolled up on a matching unrolling device, from which it can be unrolled once again.

9. The tape of claim 8, wherein means are provided at least at the folded side for preventing adhesion to the unrolling device.

- 10. The tape of one of the preceding claims, wherein the tape is at least 3 to 4 cm wide in the not folded state.
- 11. The tape of one of the preceding claims, wherein two lateral longitudinal sections, which are perforated, are provided in each case at side regions.
- 12. The tape of one of the preceding claims, wherein a non-adhering central strip is provided and the perforated longitudinal section is at a distance from the central strip.
- 13. The tape of one of the preceding claims, wherein the backing, the adhesive layer and the protective film, which can be pulled off, are perforated.
- 14. The tape of one of the preceding claims, wherein the backing consists of a material, particularly of an open-pored material, which exhibits good adhesion properties for plaster.
- 15. The tape of one of the preceding claims, wherein the perforated section has openings with an average diameter of at least 3 millimeters.
- 16. The tape of claim 15, wherein the openings are essentially circular, polygonal or oval.



17. A dispenser for a rolled-up pressure-sensitive tape of one of the claims 1 to 16, which essentially surrounds the roll of adhesive tape and has at least one outlet slot for the tape.

18. The dispenser of claim 17, wherein cardboard is used as material.

ADDCI